

Specifications

	MANUAL SAWMILLS	LT10	LT15START	LT15	LT15GO	LT15WIDE	LX150	LX250
DIMENSIONS <small>(With Trailer Package)</small>	Length	14'4" (4.4 m)	13'6" (4.1 m)	20'4" (6.2 m)	22'3" (6.8 m)	20'4" (6.2 m)	22' (6.7 m)	18'3" (5.6 m)
	Width	5'4¾" (1.6 m)	6'3" (1.9 m)	6'3" (1.9 m)	6'3" (1.9 m)	6'11" (2.1 m)	8'6" (2.6 m)	9'6" (2.9 m)
	Height (max head position)	5'10¾" (1.8 m)	6'6" (2 m)	8'6" (2.6 m)	9'5" (2.9 m)	10' (3 m)	7'4" (2.3 m)	8'7" (2.7 m)
	Weight (w/ heaviest power options)	660 lbs (299 kg)	920 lbs (417 kg)	1,200 lbs (544 kg)	1,850 lbs (839 kg)	1,530 lbs (694 kg)	2,500 lbs. (1,134 kg)	3,420 lbs. (1,551 kg) (with pallet for shipping)
MAXIMUM CUTTING CAPACITIES¹	Log Lengths	11' (3.3 m) or no limit	11' (3.3 m) or no limit	17'8" (5.4 m) or no limit	17'8" (5.4 m)	17'8" (5.4 m) or no limit	18'6" (5.7 m) or no limit	13' (4 m)
	Log Diameter	24" (610 mm)	28" (710 mm)	28" (710 mm)	28" (710 mm)	36" (914 mm)	36" (914 mm)	55" (1,397 mm)
	Production Rates²	up to 160 bd ft/hr (.37m ³ /hr)	up to 240 bd ft/hr (.57m ³ /hr)	up to 320 bd ft/hr (.75m ³ /hr)	up to 320 bd ft/hr (.75m ³ /hr)	up to 375 bd ft/hr (.88m ³ /hr)	up to 375 bd ft/hr (.88m ³ /hr)	N/A
	Power Selections	10 HP (7.5 kW) Gasoline	14 HP (10.4 kW) Recoil Gas Start	19 HP (14.1 kW) Gas 25 HP (18.6 kW) Gas 10 HP (7.5 kW) Diesel 17 HP (12.7 kW) Diesel 10 HP (7.5 kW) Elec 1PH 10 HP (7.5 kW) Elec 3PH	19 HP (14.1 kW) Gas 25 HP (18.6 kW) Gas 10 HP (7.5 kW) Diesel 17 HP (12.7 kW) Diesel	25 HP (18.6 kW) Gas 17 HP (12.7 kW) Diesel 10 HP (7.5 kW) Elec 1PH 10 HP (7.5 kW) Elec 3PH	25 HP (18.6 kW) Gas	38 HP (28.3 kW) Gas 15 HP (11 kW) Elec 3PH
OTHER SPECIFICATIONS	Blades (thickness x width)	.042" (1 mm) x 1.25" (32 mm)	.042" (1 mm) x 1.25" (32 mm)	.042" (1 mm) x 1.25" (32 mm)	.042" (1 mm) x 1.25" (32 mm)	.042" (1 mm) x 1.25" (32 mm)	.042" (1 mm) x 1.25" (32 mm) .045" (1.1 mm) x 1.25" (32 mm) .045" (1.1 mm) x 1.5" (38 mm)	.042" (1 mm) x 1.25" (32 mm) .045" (1.1 mm) x 1.25" (32 mm) .045" (1.1 mm) x 1.5" (38 mm)
	Feed System	Manual Push	Push Feed Bar	Hand Crank, Power Feed (Opt)	Hand Crank, Power Feed (Opt)	Hand Crank, Power Feed (Opt)	12V Electric-Power Feed	12V Electric-Power Feed
	Up/Down	Manual	Hand Crank	Hand Crank	Hand Crank	Hand Crank	12V Electric	12V Electric
	Trailer Package	N/A	Optional	Optional	Standard	N/A	N/A	N/A
	Bed Extensions³	Unlimited 7' (2.1 m) sections	Unlimited 6'8" (2 m) sections	Unlimited 6'8" (2 m) sections	Not available	Unlimited 6'8" (2 m) sections	Unlimited 6'1" (1.8 m)	Not available
	Stainless Steel Bed Sleeves	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	Log Turner	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	Toeboards	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	Board Return	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	SimpleSet Networks	N/A	N/A	N/A	N/A	N/A	Optional	Standard
	Manual Winch	N/A	N/A	N/A	N/A	Optional	N/A	N/A
	Debarker	N/A	N/A	N/A	N/A	N/A	Optional	N/A
	Log Loader	N/A	N/A	N/A	N/A	Winch	N/A	N/A
Blade Lubrication	Water lube - manual valve	Water lube - Convenient on/off	Water lube - Convenient on/off	Water lube - Convenient on/off	Water lube - Convenient on/off	Water lube - Convenient on/off	Water lube - Convenient on/off	
Warranty/Money Back Guarantee	2 yr / 30 day Limited	2 yr / 30 day Limited	2 yr / 30 day Limited	2 yr / 30 day Limited	2 yr / 30 day Limited	2 yr / 30 day Limited	2 yr / 30 day Limited	

1 Maximum log capacity for a basic LT10 is 3,500 lbs (1,587 kg), LT15START, LT15, LT15GO is 4,000 lbs (1,814 kg), and LT15WIDE, LT28 and larger mills are 4,400 lbs (1,996 kg).

2 Published production numbers are conservative averages and will vary. Documented, higher productions have been achieved.

3 Loading of logs heavier than 4,400 lbs (1,996 kg) [BX equipped mills] requires auxiliary log handling equipment.

* Specifications are subject to change without notice.

MANUAL SAWMILLS	LT28	LT35
Length	26'2" (8 m)	26'2" (8 m)
Width	6'6" (2 m)	6'6" (2 m)
Height (max head position)	8'5" (2.6 m)	8'5" (2.6 m)
Weight (w/ heaviest power options)	2,420 lbs (1,098 kg)	3,081 lbs (1,398 kg)
Log Lengths	21' (6.4 m) & up to 45' (13.7 m) w/BX	21' (6.4 m) & up to 45' (13.7 m) w/BX
Log Diameter	32" (810 mm)	32" (810 mm)
Production Rates ²	up to 350 bd ft/hr (.82m ³ /hr)	up to 375 bd ft/hr (.88m ³ /hr)
Power Selections	19 HP (14.1 kW) Gas 25 HP (18.6 kW) Gas 17 HP (12.7 kW) Diesel	25 HP (18.6 kW) Gas 24 HP (17.9 kW) Diesel
Blades	.042" (1 mm) thick x 1.25" (32 mm) wide	.045" (1.1 mm) x 1.25" (32 mm) .042" (1 mm) x 1.25" (32 mm)
Feed System	Hand Crank, Power Feed (Opt)	12V Electric-Power Feed
Up/Down	Hand Crank	12V Electric
Trailer Package	Standard	Standard
Bed Extensions ³	6', 12', 24' (1.8 m, 3.6 m, 7.3 m) optional	6', 12', 24' (1.8 m, 3.6 m, 7.3 m) optional
Stainless Steel Bed Sleeves	Yes	Yes
Log Turner	Manual (Optional)	Manual (Optional)
Toeboards	Manual (Optional)	Manual (Optional)
Board Return	N/A	N/A
SimpleSet Setworks	N/A	Standard
Manual Winch	Optional	Optional
Debarker	N/A	Optional
Log Loader	Winch (Optional)	Winch (Opt), Hydraulic (Opt)
Blade Lubrication	Water lube - manual valve	Water lube - manual valve
Warranty/Money Back Guarantee	5 yr Chassis, 2 yr / 30 day Limited	5 yr Chassis, 2 yr / 30 day Limited

HYDRAULIC SAWMILLS *Take sawing to a higher level*

LT35 - REDEFINING AFFORDABILITY FOR HYDRAULIC SAWMILLS

LT40 - THE INDUSTRY'S SAWING WORKHORSE

LT40 SUPER - STEP UP TO HIGH PRODUCTION SAWING

LT50 - PRODUCE FASTER. PERFORM BETTER.

LT70 SUPER - OUR FASTEST SAWMILL EVER!

