FORM 382

WOOD-MIZER LUBRICANTS

The following lubricants are available from Wood-Mizer to assist you in caring for your sawmill.

ITEM TYPE	DESCRIPTION	PART NO.	QTY.	SAWMILL USE
NLGI No. 2 Lithium Grease	Amoco Rycon #2 Synthetic	P07253	1 cartridge	Recommended for: Bearings Blade Guide Arm Log Turner Blade Tensioner Handle Greasable Blade Guide Rollers
Grease Gun		P07252	each	For Use With Grease Cartridges
Contact Grease	Chemlube JT6HT (Hi-temp)	A20463	1 container	Recommeded for: Power Feed Drum Switch Contacts Resaw Attachment Harness Plugs
Gear Oil	Mobil SHC 634 Synthetic	L04869-4	8 ounces	Recommended for: Up/Down Gearbox Oil LT70HD Power Feed Gearbox Oil
Automatic Transmission Fluid	Dexron III ATF or Exxon Univis HVI 26	P12742 or P12823	1 quart 1 gallon	Recommended for: Vertical Mast Rails Pivot Pins Chains Track Wiper Drive-Side Cylinder Bearing
Brake Fluid		P10331	1 pint	Recommended for: Electric and Surge Brake Trailers
Hydraulic Fluid	Conoco MV32	006397	1 gallon	Recommended for: All-weather applications
	Exxon Univis HVI 13	P12822	1 gallon	Recommended for: Cold-weather applications
	Amoco Rycon Oil MV	P10330	5 gallons	Recommended for: Tropical Applications Continuous Run Applications
Cleaning Solvent	WD-40 Oil	P10333	15 ounces	Miscellaneous
Rust-Inhibiting Spray	Sherwin-Williams P.D.R.P. #710	L04877	12 ounces	Recommended for: Bed-x rails when bed-x is not in use
Teflon Spray	Gunk L508	004872	6 ounces	Blade Tensioner Rods
Hydrostatic Oil	Shell TTF-SB	040642 or 048938	32 ounces 4 litres (1.05 gallons)	Hydrostatic Up/Down & Feed system (1 1/2 gallon capacity)
Ballscrew Lubricant (LT300 Only)	TriGEL-450R	042399	10cc	LT300 Up/Down Ballscrew